

# MDG

Creating better fog since 1980

## M3e

The Maximum output generator  
that take your fog to the MAX...

**e**volution

**e**asy control

**e**nergy **e**fficient

**e**xceptional results



... just got better.

Nice work.

## TECHNICAL DATA

- Single high output
- 100% Duty Cycle
- Variable fog output
- Last operation mode memory
- Recordable failure / anomaly logs
- Firmware upgradable
- Automatic Purging System™ (APS™)
- Maximum Gas pressure input: 4.14 Bar (60 PSI)
- 3 standard USITT DMX512 channels, XLR-5, 1 input, 1 output.
- RDM compliant device.
- USB 2.0 Link connector (control)

### M3e

Maximum fog output (per minute)	150 m <sup>3</sup> (5,300 ft <sup>3</sup> )
Fluid consumption (per hour at 2.76 bar/40 psi)	1,8 L (53 oz / 0.475 US gallon)
Gas type	CO <sub>2</sub> or N <sub>2</sub>
CO <sub>2</sub> consumption (per hour at 2.76 bar/40 psi)	1,6 kg (3.5 lb)
Control	4-button LCD user interface, DMX XLR-5 connectors, RDM compliant device
Reservoir capacity	2,5 L (0.66 US gallon)
Automatic Purging System (APS)	Standard feature
Fog colour	Pure white
Partical size	0,5 - 0,7 micron
Warm-up time (maximum)	8 minutes
Fluid type (M.S.D.S. available on request)	MDG Neutral Fluid
Operating voltage	100-250 VAC, 50/60 Hz single phase
Power consumption	715 W
Dimension	Length Width Height
	61 cm (24") 18 cm (7") 30 cm (12")
Weight	15.62 kg (35 lb)
Shipping weight (without flight case)	20.42 kg (45 lb)
Shipping weight (with flight case)	29.12 kg (64 lb)
Approval	CE, CSA and UL

## FLUID

### MDG Neutral Fluid

Safe, non-toxic, with the longest hanging time. Available in 4 L (1 US gallon), 5 L (Europe only), 20 L (5.3 US gallon), 205 L (55 US gallon) and 1000 L (264 US gallon) sizes.



## ACCESSORIES

### Flight case

Durable for safe and easy transport



# MDG

Creating better fog since 1980

10301 av. Pelletier, Montréal, Québec, Canada H1H 3R2  
T (514) 272-6040 | 1-800-663-3020 | F (514) 722-3229  
info@mdgfog.com - www.mdgfog.com